



COBRA

TEXTILE REINFORCED CONCRETE HOSE








Designed for high pressure concrete pumping, Cobra Textile Reinforced Concrete Hose is constructed with a smooth highly abrasion resistant rubber liner and high-tensile textile cord reinforcements. Hose cover is made with abrasion, weather, and ozoneresistant SBR/EPDM synthetic rubber.



Recommended operating temperature range is -30°F to +180°F.

- ▶ **TUBE:** *Smooth highly abrasion resistant rubber liner.*
- ▶ **REINFORCEMENT:** *High-tensile textile cord.*
- ▶ **COVER:** *Black. Smooth, abrasion, weather and ozone resistant SBR/EPDM synthetic rubber.*
- ▶ **TEMPERATURE:** *-30°F to +180°F.*

Meets/exceeds ASME b30.27-2019

Part Number	 I.D. (inch)	 O.D. (inch)	 Working Pressure (PSI)	 Burst Pressure (PSI)	 Plies of Reinforcement	 Minimum Bend Radius (inch)	 Lbs./Ft.
AH-2-COBRA	2"	2.8"	1232 PSI	2464 PSI	4	20"	1.41
AH-2.5-COBRA	2-1/2"	3.3"	1232 PSI	2464 PSI	6	25"	2.04
AH-3-COBRA	3"	4.0"	1232 PSI	2464 PSI	6	30"	2.75
AH-3.5-COBRA	3.5"	4.5"	1232 PSI	2464 PSI	6	35"	3.47
AH-4-COBRA	4"	5.1"	1232 PSI	2464 PSI	6	40"	3.98