



MUD DAUBER

CONCRETE, PLASTER & GROUT HOSE








Austin Hose's Concrete, Plaster, and Grout Hose is constructed using a smooth, highly abrasion-resistant rubber lining and high-tensile textile reinforcements. The cover is smooth, abrasion and weather-resistant rubber and is available in black or tan.



The recommended temperature range is -30°F to +180°F.

MULTIPLE END COMBINATIONS AVAILABLE

Metric • Heavy Duty • NTP
Reducing & Non Reducing

Part Number	 I.D. (inch)	 O.D. (inch)	 Working Pressure (PSI)	 Burst Pressure (PSI)	 Plies of Reinforcement	 Minimum Bend Radius (inch)	 Lbs./Ft.
AH-1.25-CPG	1-1/4"	1.9"	1232 PSI	2464 PSI	4	15"	0.9
AH-1.5-CPG	1-1/2"	2.2"	1232 PSI	2464 PSI	4	15"	1.1
AH-2-CPG	2"	2.8"	1232 PSI	2464 PSI	4	20"	1.4
AH-1.25-CPG-TAN	1-1/4"	1.9"	1232 PSI	2464 PSI	4	15"	0.9
AH-1.5-CPG-TAN	1-1/2"	2.2"	1232 PSI	2464 PSI	4	15"	1.1
AH-2-CPG-TAN	2"	2.8"	1232 PSI	2464 PSI	4	20"	1.4