









ROUGHNECK TANK TRUCK HOSE

Roughneck is Powertrack's 150# Tank Truck Suction and Discharge Hose, specifically designed for petroleum and oil applications. Engineered with superior durability and performance in mind, Roughneck ensures safe and efficient handling of petroleum products in tank truck operations. Trust Roughneck to deliver exceptional quality and meet the demanding needs of your industry.



- ▶ **TUBE:** *Black Nitrile synthetic rubber RMA class A (High Oil Resistance)*
- ▶ **REINFORCEMENT:** *Spiral-plied synthetic fabric with dual helix wire*
- ▶ **COVER:** *Black (or Red) abrasion, oil, weather & ozone resistant rubber (Corrugated cover)*
- ▶ **TEMPERATURE:** *-20°F to +180°F*

Part Number	 I.D. (inch)	 O.D. (inch)	 Working Pressure (PSI)	 Standard Length (feet)	 Bend Radius (inch)	 Lbs./Ft.
AH-1-TT	1.00"	1.46"	150 PSI	200'	6"	0.59 Lbs/Ft
AH-1.25-TT	1.25"	1.73"	150 PSI	200'	8"	0.74 Lbs/Ft
AH-1.5-TT	1.50"	1.97"	150 PSI	200'	12"	0.85 Lbs/Ft
AH-2-TT	2.00"	2.56"	150 PSI	200'	16"	1.38 Lbs/Ft
AH-2.5-TT	2.50"	3.03"	150 PSI	200'	18"	1.64 Lbs/Ft
AH-3-TT	3.00"	3.62"	150 PSI	200'	20"	2.27 Lbs/Ft
AH-4-TT	4.00"	4.76"	150 PSI	200'	28"	3.61 Lbs/Ft
AH-6-TT	6.00"	6.85"	150 PSI	100'	47"	6.22 Lbs/Ft
AH-8-TT	8.00"	9.06"	150 PSI	100'	63"	9.49 Lbs/Ft
AH-10-TT	10.00"	11.22"	150 PSI	40'	79"	15.24 Lbs/Ft