



# T-REX STEEL REINFORCED CONCRETE HOSE








Designed for high pressure concrete pumping, T-Rex Steel Reinforced Concrete Hose is constructed with a smooth highly abrasion resistant rubber liner and high-tensile steel wire spiral reinforcements. Hose cover is made with abrasion, weather, and ozoneresistant SBR/EPDM synthetic rubber.



*Recommended operating temperature range is -30°F to +180°F.*

- ▶ **TUBE:** *Smooth highly abrasion resistant rubber liner.*
- ▶ **REINFORCEMENT:** *High-tensile textile steel wire spiral.*
- ▶ **COVER:** *Black. Smooth, abrasion, weather and ozone resistant SBR/EPDM synthetic rubber.*
- ▶ **TEMPERATURE:** *-30°F to +180°F.*

*Meets/exceeds ASME b30.27-2019*

Part Number	 I.D. (inch)	 O.D. (inch)	 Working Pressure (PSI)	 Burst Pressure (PSI)	 Plies of Reinforcement	 Minimum Bend Radius (inch)	 Lbs./Ft.
AH-2-TREX	2"	2.7"	1450 PSI	2900 PSI	4	24"	1.7
AH-2 1/2-TREX	2-1/2"	3.4"	1450 PSI	2900 PSI	4	28"	2.5
AH-3-TREX	3"	4.0"	1450 PSI	2900 PSI	4	36"	3.4
AH-4-TREX	4"	5.0"	1450 PSI	2900 PSI	6	42"	5.7
AH-5-TREX	5"	6.1"	1450 PSI	2900 PSI	6	50"	6.5