Bull Hose AIR HOSE

The ultimate solution for high pressure air applications requiring exceptional strength and performance. This wire braid hose is tough as a bull. With a pressure rating of 600 PSI,



Bull hose is engineered to handle the toughest air-moving tasks, including those that involve large volume air transfer. Whether working in construction, mining, or any other demanding environment, Bull hose provides reliable and efficient high pressure air flow.

TUBE: Tube is oil-resistant Nitrile blend

► **REINFORCEMENT**: Steel wire with brass coating

COVER: Yellow pin-picked, abrasion, ozone, and weather resistant CPE

► TEMPERATURE: -40°F to +248°F

► SAFETY FACTOR: 4:1

Part Number	I.D. (inch)	O.D. (inch)	Working Pressure (PSI) @ 68° F	Maximum Length (feet)	Bend Radius (inch)	Lbs./Ft.
AH-1-BULL-600	1″	1.44"	600 PSI	100′	12"	0.60 Lbs/Ft
AH-1.5-BULL-600	1-1/2"	1.96"	600 PSI	100′	20"	1.01 Lbs/Ft
AH-2-BULL-600	2″	2.49"	600 PSI	100′	25″	1.88 Lbs/Ft
AH-2.5-BULL-600	2-1/2"	3.06"	600 PSI	100′	30″	2.15 Lbs/Ft
AH-3-BULL-600	3″	3.54"	600 PSI	100′	39″	2.69 Lbs/Ft
AH-4-BULL-600	4"	4.63"	600 PSI	100′	47"	3.36 Lbs/Ft

The working pressure (W.P.) varies with temperature.

