

# Diamondback








## HYDRAULIC HOSE

2SC



High pressure service with tight bends for petroleum and water-based hydraulic fluids. Excellent impulse performance and flexibility exceeding SAE 100R2 and SAE 100R16 standards (sizes -10, -12 and -16 meet or exceed SAE 100R17). MSHA approved.

<b>TUBE</b>	Oil Resistant, Synthetic Rubber
<b>REINFORCEMENT</b>	Two Braids of High-Tensile Steel Wire
<b>COVER</b>	Environment Resistant Synthetic Rubber
<b>TEMPERATURE</b>	-40°F to +212° (-40°C to 100°C)

Part Number	 I.D. (inch)	 O.D. (inch)	 Working Pressure (PSI)	 Burst Pressure (PSI)	 Reel Length (feet)	 Bend Radius (inch)	 Weight (Lbs/Ft)
AH-2SC-04	1/4"	0.52"	5,800 PSI	23,200 PSI	550'	1.97"	0.19 Lbs/Ft
AH-2SC-06	3/8"	0.67"	5,000 PSI	20,000 PSI	385'	2.56"	0.28 Lbs/Ft
AH-2SC-08	1/2"	0.81"	4,000 PSI	16,000 PSI	330'	3.54"	0.36 Lbs/Ft
AH-2SC-10	5/8"	0.95"	3,625 PSI	14,500 PSI	220'	3.94"	0.44 Lbs/Ft
AH-2SC-12	3/4"	1.11"	3,120 PSI	12,480 PSI	220'	4.72"	0.57 Lbs/Ft
AH-2SC-16	1"	1.40"	3,000 PSI	12,000 PSI	165'	5.91"	0.81 Lbs/Ft



**POWERTRACK** USA

[nationalsales@powertrackhose.com](mailto:nationalsales@powertrackhose.com)