

TRACK

A premium rubber water discharge hose tougher than your standard PVC or Nitrile lay-flat discharge. Commonly used as a "chiller hose", it offers a 150 PSI working pressure but has

no helix wire, making it resistant to being crushed.

POWERIE ES

▶ **TUBE**: Black. Synthetic rubber compound,

resistant to waste water up to 10 pH.

▶ **REINFORCEMENT:** High tensile textile cord fabric.

COVER: Black. Synthetic rubber, wrapped type, abrasion water resistant.

TEMPERATURE: -22°F to +154°F

SAFETY FACTOR: 3:1

Part Number	I.D. (inch)	O.D. (inch)	Working Pressure (PSI)	Standard Length (feet)	Lbs./Ft.
AH-2-WD	2"	2.32"	150 PSI	100′	0.59 Lbs/Ft
AH-3-WD	3″	3.3"	150 PSI	100′	0.89 Lbs/Ft
AH-4-WD	4"	4.33"	150 PSI	100′	1.17 Lbs/Ft
AH-6-WD	6″	6.37"	150 PSI	100′	2.16 Lbs/Ft
AH-8-WD	8″	8.54"	150 PSI	100′	4.15 Lbs/Ft
AH-10-WD	10"	10.55″	150 PSI	100′	5.61 Lbs/Ft

