








Stingray WATERBLAST



- ▶ **TUBE:** Oil Resistant Synthetic Rubber
- ▶ **REINFORCEMENT:** Multiple Plies of Spiral Wires
- ▶ **COVER:** Oil and Weather Resistant Synthetic Rubber
- ▶ **TEMPERATURE:** -40°F to +212°F
- ▶ **SAFETY FACTOR:** 2.5:1



Part Number	 I.D. (inch)	 O.D. (inch)	 Working Pressure (PSI)	 Burst Pressure (PSI)	 Bend Radius (inch)	 Reinforce (Plies)	 Weight (lbs/ft)
— YELLOW —							
AH-6-WB-12K	3/8"	0.89"	12,000 PSI	30,000 PSI	7.1"	4 ply	0.81 lbs/ft
AH-8-WB-10K	1/2"	0.96"	10,000 PSI	25,000 PSI	9.1"	4 ply	0.81 lbs/ft
AH-12-WB-10K	3/4"	1.25"	10,000 PSI	25,000 PSI	11.8"	4 ply	1.01 lbs/ft
AH-16-WB-10K	1"	1.5"	10,000 PSI	25,000 PSI	13.4"	4 ply	1.34 lbs/ft
AH-20-WB-10K	1-1/4"	1.97"	10,000 PSI	25,000 PSI	18.1"	6 ply	2.28 lbs/ft
— GREEN —							
AH-6-WB-18K	3/8"	0.89"	18,000 PSI	45,000 PSI	7.1"	4 ply	1.01 lbs/ft
AH-8-WB-16K	1/2"	0.96"	16,000 PSI	40,000 PSI	9.1"	4 ply	0.84 lbs/ft
AH-12-WB-15K	3/4"	1.42"	15,000 PSI	37,500 PSI	11.8"	6 ply	1.62 lbs/ft

